



PINS

Finger-tip matting

16/07/2014

STANDARD MATTING

FEATURES

Finger-tip design.
Non-slip surface.

ADVANTAGES

- Non-slippery
- Thermal and acoustic insulation
- Reduces tiredness and helps to increase productivity
- Comfortable
- Enable an efficient footwear soles cleaning

BENEFITS

- Safety
- Comfort
- Performance
- Cleanliness

APPLICATIONS

Shoe cleaning mats.

Floor mats at work stations.


Heavy transit areas.

www.trelleborg.com/elastomerlaminates

MECHANICAL, PHYSICAL AND CHEMICAL PROPERTIES

	Measured characteristics	Standard	Value	
MECHANICAL				
	Rubber compound		SBR/NR	
	Hardness	ASTM D2240	65 ± 5	Shore A
	Abrasion resistance (5 N)	ISO 4649	≤ 200	mm ³
	Residual indentation	EN ISO 24343	≤ 0.15	mm
	Dimensional stability	EN ISO 23999	± 0.3	%
	Sound insulation	ISO 10140-3	12	dB
CHEMICAL RESISTANCE				
	Common cleaning products	EN 423	Good	

PROFILE



Finger-tip (MF)

DIMENSIONS

Colour	Thickness (mm)		Width (mm)		Length (m)		Weight (kg/m ²)	Pattern
●	10	± 1	1000	± 2 %	10	± 2 %	7.5	MF
●	16	± 1.4	1000	± 2 %	8	± 2 %	12.5	MF

IDENTIFICATION

Branding	Without.
Back face	With support pivot pins.
Packaging	In rolls.
Wrapping	Black polyethylene film.
Labelling	Self-adhesive label indicating product name, dimensions, area in m ² , nominal weight, and product code to allow product traceability.